

CONVENTIONAL MILLING MACHINES






Series FCQ

HIGHLIGHTS

- Universal vertical milling head swivelling in 45 and 90 degree
- 3-axis digital position display
- Automatic feed in all 3 axes
- Universal milling machines with cross slide versatile use



TECHNICAL DATA AT A GLANCE

Machine type	 mm	 mm	 min ⁻¹	 kg	 kW
FCQ 1370x320	1.000x380x400	1.370x320	35-1.660	1.950	2,7
FCQ 1600x360	1.300x320x450	1.600x360	60-1.800	2.800	4/5,5

Further information on the machine series and numerous accessories can be found on our website:
<https://www.wagner-maschinen.de/fraesen>

UNIVERSAL MILLING MACHINE FCQ 1370x320/ FCQ 1600x360

FCQ 1370x320 with 3-axis digital display with swivelling arm **Order no.: 610255**

FCQ 1600x360 with 3-axis digital display with swivelling arm **Order no.: 610264**



ALL HIGHLIGHTS AT A GLANCE

- Universal vertical milling head can be swivelled in 2 axes
- 3-axis digital readout
- Automatic feed in all 3 axes
- Complete electrical equipment 400 V./50 Hz.
- Complete coolant system
- Cross slide manually positionable
- Separate horizontal spindle
- Automatic central lubrication
- Stepless feed rates
- Rapid traverse in the X, Y and Z axes
- Operating tool and documentation

Further information on the machine series and numerous accessories can be found on our website:

<https://www.wagner-maschinen.de/fraesen>

TECHNICAL DATA

- Table clamping surface
1.370x320 mm/1.600x360 mm
- T-slot width 18 mm
- Distance of the T-slots 80 mm
- Table load 400 kg/ 500 kg
- Distance table/spindle nose
max./min. 260/660/196/648 mm
- X-axis travel 1.000 mm/1.300 mm
- Y-axis travel 380 mm/320 mm
- Z-axis travel 400 mm/450 mm
- Manual cross feeds 460 mm/550 mm
- Feed, infinitely variable
- Longitudinal/transverse
20- 500/30-750 mm/min/30-830 mm/min
- Vertical 23-625 mm/min / 15-375 mm/min
- Rapid traverse: longitudinal and transverse
- Rapid traverse vertical
- Tool holder
DIN 2080 H+V ISO 40/ISO 50
- Adjustment range vertical milling head 360°
- Speed levels/range H/V,
min⁻¹ 12-35-1.500/11-45-1.660/
27-60-1.750/60-1.800
- Spindle motor Drive power
H/V 2,7/4 kW/5,5 kW
- Dimensions 1.820x1.680x1.860 mm/
2.560x2.800x2.000 mm
- Weight, ca. 1.950 kg/2.800 kg

STANDARD EQUIPMENT

- Complete electrical equipment 400 V./50 Hz.
- Complete coolant system
- Automatic feed in all 3 axes
- Cross slide can be positioned manually
- 3-axis digital position indicator
- Separate horizontal spindle
- Automatic centralised lubrication
- Infinitely variable feed rates
- Rapid traverse in the X, Y and Z axes
- Operating tool and documentation
- CE standard

DETAIL PICTURES



Further information on the machine series and numerous accessories can be found on our website:
<https://www.wagner-maschinen.de/fraesen>

We reserve the right to make design changes in the course of technical improvements. Illustrations, dimensions and weights are not binding.